

## FOXALUC (FO-202)

### Acrylic Emulsion

**DESCRIPTION** FOXALUC is good quality emulsion based on styrene acrylic resin that contains no lead or mercury.

---

#### PRINCIPLE CHARACTERISTIC

- Applicable for interior or exterior wall.
  - Good adhesion
  - Good durability.
  - Fungus and weather resistant, and not smelly.
  - Good hiding power properties.
- 

#### RECOMMENDED USE

Suitable for new / previously painted surfaces such as bricks, asbestos, cement plaster, hardboard, plywood, concrete block, etc.

---

#### SYSTEM SPECIFICATION

Primer ( 1 coat ) : FOXASEALER WB : FO-101  
Finish ( 2-3 coat ) : FOXALUC : FO-202

---

#### SPECIFICATION DATA AT 20°C

Gloss	Flat
Colours	See colour card
Specific gravity	1.40 ± 0.10 kg/litre
Solids by volume	30 ± 2%
Coverage theoretical	Varies considerably according to the roughness And porosity of the surface 8 – 10 m <sup>2</sup> / litre (on Smooth surfaces of average porosity)
Drying time	Touch dry : 10 minutes (depend on temperature and humidity) Hard dry : 2 hours
Painting interval	Min. 2 hours
Shelf life	12 month (cool and dry place)

---

#### SURFACE PREPARATION

- Surface must be sound, clean, dry, free from all defective or poorly adhering material, dirt, grease, wax, and be rubbed down thoroughly using a suitable abrasive paper and dusted off.
  - A good surface preparation is improve performance / life service.
  - Surface after thorough preparation should be sealed with FOXASEALER.
  - NOTE : Do not apply during wet weather.
- 

#### INSTRUCTION FOR USE

- Stir well before use, to achieve uniformity of colour and good homogeneity.
  - It is recommended to apply two (2) layers, in order to get better result.
  - Clean all equipment with clean water immediately after use.
-

## RECOMMENDED THINNING

Method of application	Air Spray	Roller/Brush
Thinner No	Water	Water
Thinning	10 – 15 %	0 – 10 %
Nozzle orifice	1.5 - 2 mm	-
Nozzle pressure	3-4 bar / 43-57 psi	-

---

## SAFETY PRECAUTION

- Keep container tightly close and keep out from the children.
- Keep away from food, drink and animal feeding stuff.
- Care must be taken when transporting paint. Keep container in a secure up - right position.
- Avoid contact with the skin and eyes.
- Wear suitable protective clothing such as overalls, goggles, dust mask and gloves.
- Ensure that there is adequate ventilation in the area where the product is being applied.
- Do not breathe the vapour or spray.
- Dispose of any paint waste in accordance with the appropriate Environmental Quality Regulations.

---

## HEALTH AND SAFETY

For detailed information on the health and safety hazards and precaution for use of this product, please see the **MATERIAL SAFETY DATA SHEET**.

---

## PACKING SIZE AND STORAGE

Packing size  
Storage

5 and 20 litres.  
The product must be storage in accordance with national regulation. Preferred storage conditions are the keep the containers in the dry space provided with adequate ventilation. The container should be sealed tightly.