

**FOXA ALKALI (OD-100)**  
**Alkali Resistance Primer**

<b>DESCRIPTION</b>	Water thinnable alkali resistance sealer based on acrylic dispersion.														
<b>CHARACTERISTIC</b>	<ul style="list-style-type: none"><li>• Level the absorption of untreated substrates.<ul style="list-style-type: none"><li>• Unsaponifiable.</li></ul></li><li>• Recoatable with dispersion an alkyd resin paints.</li><li>• Wall paper application on top possible.</li><li>• Fixes powdering or chalking old layer on porous substrate.</li><li>• Prevents discolouring.</li><li>• Good alkali resistance properties.</li></ul>														
<b>RECOMMENDED USE</b>	As a sealing agents for interior and exterior wall coating. Suitable for use on old or fully cured new cement surfaces such as render, and formwork to prevent alkali attack on the Finish coats.														
<b>SPECIFICATION DATA (At 20° C)</b>	<table><tr><td>Gloss</td><td>Flat</td></tr><tr><td>Colours</td><td>Milky ; driers colourless</td></tr><tr><td>Specific gravity</td><td>1.0 ± 0.1 kg/litre</td></tr><tr><td>Coverage theoretical</td><td>8 – 10 m<sup>2</sup>/litre, depending on the absorption of the surface.</td></tr><tr><td>Touch dry</td><td>2 hours</td></tr><tr><td>Painting interval</td><td>6 hours</td></tr><tr><td>Shelf life</td><td>9 month (cool and dry place)</td></tr></table>	Gloss	Flat	Colours	Milky ; driers colourless	Specific gravity	1.0 ± 0.1 kg/litre	Coverage theoretical	8 – 10 m <sup>2</sup> /litre, depending on the absorption of the surface.	Touch dry	2 hours	Painting interval	6 hours	Shelf life	9 month (cool and dry place)
Gloss	Flat														
Colours	Milky ; driers colourless														
Specific gravity	1.0 ± 0.1 kg/litre														
Coverage theoretical	8 – 10 m <sup>2</sup> /litre, depending on the absorption of the surface.														
Touch dry	2 hours														
Painting interval	6 hours														
Shelf life	9 month (cool and dry place)														
<b>SURFACE PREPARATION</b>	Substrate must be free of any contamination, Substrate containing lime and cements should be properly dried, hard and fully reacted.														
<b>INSTRUCTION FOR USE</b>	<ul style="list-style-type: none"><li>• Stir well before use of paint.</li><li>• Method of application                      Brush / roller</li><li>• Thinner                                              Tap water</li><li>• Volume of thinner                              0 – 5%</li></ul>														
<b>SAFETY PRECAUTION</b>	<ul style="list-style-type: none"><li>• Avoid contact with the skin and eyes.</li><li>• Wear suitable protective clothing such as overalls, goggles, dust mask and gloves.</li><li>• Ensure that there is adequate ventilation in the area where the product is being applied.</li><li>• Do not breathe the vapour or spray.</li></ul>														
<b>HEALTH AND SAFETY</b>	For detailed information on the health and safety hazards and precaution for use of this product, please see the <b>MATERIAL SAFETY DATA SHEET</b> .														
<b>PACKING SIZE &amp; STORAGE</b>	Packing size 5 and 20 litres. Storage The product must be storage in accordance with national regulation. Preferred storage conditions are the keep the containers in the dry space provided with adequate ventilation. The container should be sealed tightly.														

