

FOXSEALER WB (OD-101)

Water Based Sealer Primer

DESCRIPTION	Water thinnable sealer based on acrylic dispersion.	
CHARACTERISTIC	<ul style="list-style-type: none">• Level the absorption of untreated substrates.• Unsaponifiable.• Recoat able with dispersion and alkyd resin paints.• Wall paper application on top possible.• Fixes powdering or chalking old layer on porous substrate.• Prevents discolouring.• Good alkali resistance properties.	
RECOMMENDED USE	As a sealing agent for interior and exterior wall coating.	
SPECIFICATION DATA AT 20°C	Gloss	Flat
	Colours	Milky ; driers colourless
	Specific gravity	1.0 ± 0.1 kg/litre
	Coverage theoretical	8 – 10 m ² /litre, depending on the absorption of the surface.
	Touch dry	2 hours
	Painting interval	6 hours
	Shelf life	9 month (cool and dry place)
SURFACE PREPARATION	Substrate must be free of any contamination, Substrate containing lime and cements should be properly dried, hard and fully reacted.	
INSTRUCTION FOR USE	<ul style="list-style-type: none">• Stir well before use of paint.• Method of application• Thinner• Volume of thinner	<ul style="list-style-type: none">Brush / rollerTap water0 – 5%
SAFETY PRECAUTION	<ul style="list-style-type: none">• Avoid contact with the skin and eyes.• Wear suitable protective clothing such as overalls, goggles, dust mask and gloves.• Ensure that there is adequate ventilation in the area where the product is being applied.• Do not breathe the vapour or spray.	
HEALTH AND SAFETY	For detailed information on the health and safety hazards and precaution for use of this product, please see the MATERIAL SAFETY DATA SHEET .	
PACKING SIZE AND STORAGE	Packing size	5 and 20 litres.
	Storage	The product must be stored in accordance with national regulation. Preferred storage conditions are to keep the containers in the dry space provided with adequate ventilation. The container should be sealed tightly.