

FOXAFILLER (OD-103)

Wall Filler

DESCRIPTION	Wall putty based on acrylic emulsion.														
CHARACTERISTIC	<ul style="list-style-type: none">• Free of alkali.• Easy to apply / smear with putty knife.• Easy to scour after and the surface will be smooth and soft• Good adhesion														
RECOMMENDED USE	For fill the hole of wall, and make flattened the surface.														
SPECIFICATION DATA AT 20°C	<table border="1"><tr><td>Gloss</td><td>Flat</td></tr><tr><td>Colours</td><td>White</td></tr><tr><td>Specific gravity</td><td>1.60 ± 0.20 kg/litre</td></tr><tr><td>Coverage theoretical</td><td>5 – 6 m²/litre,(depend on surface and method of application).</td></tr><tr><td>Drying time</td><td>Touch dry : 30 minutes Hard dry : 2 hours</td></tr><tr><td>Painting interval</td><td>Min 1 hours Max. 2 days</td></tr><tr><td>Shelf life</td><td>10 month (cool and dry place)</td></tr></table>	Gloss	Flat	Colours	White	Specific gravity	1.60 ± 0.20 kg/litre	Coverage theoretical	5 – 6 m ² /litre,(depend on surface and method of application).	Drying time	Touch dry : 30 minutes Hard dry : 2 hours	Painting interval	Min 1 hours Max. 2 days	Shelf life	10 month (cool and dry place)
Gloss	Flat														
Colours	White														
Specific gravity	1.60 ± 0.20 kg/litre														
Coverage theoretical	5 – 6 m ² /litre,(depend on surface and method of application).														
Drying time	Touch dry : 30 minutes Hard dry : 2 hours														
Painting interval	Min 1 hours Max. 2 days														
Shelf life	10 month (cool and dry place)														
SURFACE PREPARATION	<ul style="list-style-type: none">• All surface should be clean, sound, smooth, dull and dry before paint is applied.• Threat peeling, loose or blistering paint.• Remove any oil, dust and stain, dirt, meld, and mildew.• A good surface preparation is improve performance / life service.														
INSTRUCTION FOR USE	<ul style="list-style-type: none">• Stir well before use, to achieve uniformity of colour and good homogeneity.• Smear on porous wall surface by spatula or putty knife and after full cure Softened /spreaded with rough scour, soft.														
SAFETY PRECAUTION	<ul style="list-style-type: none">• Keep container tightly close and keep out from the children• Keep away from food, drink, and animal feeding stuff.• Care must be taken when transporting paint. Keep container is a secure up-right position.• Avoid contact with skin and eyes.• Wear suitable protective clothing such as overalls, goggles, dust mask and gloves.• Ensure that there is adequate ventilation in the area where the product is being applied.• Do not breathe the vapour or spray.														
HEALTH AND SAFETY	For detailed information on the health and safety hazards and precaution for use of this product, please see the MATERIAL SAFETY DATA SHEET .														
PACKING SIZE & STORAGE	<table border="1"><tr><td>Packing size</td><td>5 and 20 litres.</td></tr><tr><td>Storage</td><td>The product must be storage in accordance with national regulation. Preferred storage conditions are the keep the containers in the dry space provided with adequate ventilation. The container should be sealed tightly.</td></tr></table>	Packing size	5 and 20 litres.	Storage	The product must be storage in accordance with national regulation. Preferred storage conditions are the keep the containers in the dry space provided with adequate ventilation. The container should be sealed tightly.										
Packing size	5 and 20 litres.														
Storage	The product must be storage in accordance with national regulation. Preferred storage conditions are the keep the containers in the dry space provided with adequate ventilation. The container should be sealed tightly.														