

FOXALINE (OX-107)

PRODUCT DESCRIPTION	A fast drying, solvent free, low viscosity liquid based on mix MMA and other Acrylate Derivatives.	
RECOMMENDED USE	Suitable use for road and traffic marking applied by manual hand application on asphalt and concrete surface. Film thickness 1,5 – 2,5 mm.	
CHARACTERISTICS	<ul style="list-style-type: none">• Fast curing.• Good exterior durability.• Abrasion resistance.	
PHYSICAL DATA	Colour	White, Yellow, Grey. Red,
	Gloss Level	Satin/ Gloss
	Volume Solid	Approx. 45%
	Dry Film Thickness	50 microns per coat
	Number of Coat	2
	Theoretical Coverage	4.5 sq.m/ℓ for 100 microns
	Flash Point	50° F
	Shelf Life	At least 6 months
SURFACE PREPARATION	Ensure surface is in sound condition. Remove any grease, dust or dirt. If necessary, wash down with water and detergent followed by a rinse with clean water. Allow to dry.	
APPLICATION DATA	Application Methods	Roll, brush, trowel
	Mixing Ratio	Add 10-15% powder to Base
	Thinner	No required
	Surface Temperature	Should be 10°C – 49°C, at least 3°C above the dew point to prevent condensation
Drying Time	Through Dry	20-30 minutes at 30°C
	Pot life	5 – 20 minutes at 30 C
SAFETY PRECAUTION	Keep away from heat, spark and open flames. Avoid breathing of vapour on skin and eye contact. Keep container closed and store in cool, ventilated area when not in use. Proper ventilation and protective measures must be provided during mixing, application and drying, to keep vapour concentration within safe limits and to protect against toxic hazard. Necessary safety equipment must be used and ventilation requirements carefully observed, especially in confined or enclosed spaces, such as tank interior and building.	

