

FOXAPRO 400 (OX-402)

High Temperature Silicone Aluminium

PRODUCT DESCRIPTION	A single component, silicone resin aluminium paint, based on a combination of silicon resin and aluminium pigment.																														
RECOMMENDED USE	High temperature service such as stack and breeching.																														
CHARACTERISTICS	<ul style="list-style-type: none"> • 100% silicone aluminium coating. • A heat resistance coating up to 400^oC. • Self priming coating. • Good weather resistance. 																														
PHYSICAL DATA	<table> <tr> <td>Colour</td> <td>Aluminium, Grey, Black</td> </tr> <tr> <td>Gloss level</td> <td>Semi Gloss</td> </tr> <tr> <td>Volume Solid</td> <td>Approx. 31%</td> </tr> <tr> <td>Dry Film Thickness</td> <td>30 microns per coat</td> </tr> <tr> <td>Number of Coat</td> <td>2</td> </tr> <tr> <td>Theoretical Coverage</td> <td>10.3 sq.m/ℓ for 30 microns</td> </tr> <tr> <td>Temperature Resistance</td> <td>Continuous : 400^oC (dry) Intermittent : 538^oC (dry)</td> </tr> <tr> <td>VOC</td> <td>329 g/ℓ</td> </tr> <tr> <td>Flash Point</td> <td>26^oC</td> </tr> <tr> <td>Shelf Life</td> <td>At least 12 months</td> </tr> </table>	Colour	Aluminium, Grey, Black	Gloss level	Semi Gloss	Volume Solid	Approx. 31%	Dry Film Thickness	30 microns per coat	Number of Coat	2	Theoretical Coverage	10.3 sq.m/ℓ for 30 microns	Temperature Resistance	Continuous : 400 ^o C (dry) Intermittent : 538 ^o C (dry)	VOC	329 g/ℓ	Flash Point	26 ^o C	Shelf Life	At least 12 months										
Colour	Aluminium, Grey, Black																														
Gloss level	Semi Gloss																														
Volume Solid	Approx. 31%																														
Dry Film Thickness	30 microns per coat																														
Number of Coat	2																														
Theoretical Coverage	10.3 sq.m/ℓ for 30 microns																														
Temperature Resistance	Continuous : 400 ^o C (dry) Intermittent : 538 ^o C (dry)																														
VOC	329 g/ℓ																														
Flash Point	26 ^o C																														
Shelf Life	At least 12 months																														
SURFACE PREPARATION	<p>Steel Dry abrasive blast in accordance with ISO – Sa 2.5 or SSPC – SP 10 “Near White”. Blast to achieve a 25 microns anchor profile of as indicated with a Keane Tator Surface Profile Comparator. Remove abrasive residue or dust from surface.</p>																														
APPLICATION DATA	<table> <tr> <td colspan="2">Application Methods</td> </tr> <tr> <td>Airless Spray</td> <td></td> </tr> <tr> <td> Nozzle Tip</td> <td>0.38 – 0.53 mm (0.015 – 0.021 inch)</td> </tr> <tr> <td> Nozzle Pressure</td> <td>10 MPa (approx. 1400 psi)</td> </tr> <tr> <td>Conventional Spray</td> <td></td> </tr> <tr> <td> Nozzle Tip</td> <td>1.8 – 2.0 mm (0.071 – 0.079 inch)</td> </tr> <tr> <td> Nozzle Pressure</td> <td>0.3 MPa (approx. 43 psi)</td> </tr> <tr> <td>Brush or Roller</td> <td>Only for touch up</td> </tr> <tr> <td>Mixing Ratio</td> <td>One component</td> </tr> <tr> <td>Thinner</td> <td>FOXANER 004</td> </tr> <tr> <td>Surface Temperature</td> <td>Should be 10^oC – 49^oC, at least 3^oC above the dew point to prevent condensation</td> </tr> <tr> <td colspan="2">Drying Time</td> </tr> <tr> <td> Touch Dry</td> <td>30 minutes at 25^oC, 20 minutes at 32^oC</td> </tr> <tr> <td> Over Coating</td> <td>16 hours at 25^oC, 12 hours at 32^oC</td> </tr> <tr> <td> For Service</td> <td>1 hour at 32^oC, followed by minimum 2 hours at 150^oC</td> </tr> </table>	Application Methods		Airless Spray		Nozzle Tip	0.38 – 0.53 mm (0.015 – 0.021 inch)	Nozzle Pressure	10 MPa (approx. 1400 psi)	Conventional Spray		Nozzle Tip	1.8 – 2.0 mm (0.071 – 0.079 inch)	Nozzle Pressure	0.3 MPa (approx. 43 psi)	Brush or Roller	Only for touch up	Mixing Ratio	One component	Thinner	FOXANER 004	Surface Temperature	Should be 10 ^o C – 49 ^o C, at least 3 ^o C above the dew point to prevent condensation	Drying Time		Touch Dry	30 minutes at 25 ^o C, 20 minutes at 32 ^o C	Over Coating	16 hours at 25 ^o C, 12 hours at 32 ^o C	For Service	1 hour at 32 ^o C, followed by minimum 2 hours at 150 ^o C
Application Methods																															
Airless Spray																															
Nozzle Tip	0.38 – 0.53 mm (0.015 – 0.021 inch)																														
Nozzle Pressure	10 MPa (approx. 1400 psi)																														
Conventional Spray																															
Nozzle Tip	1.8 – 2.0 mm (0.071 – 0.079 inch)																														
Nozzle Pressure	0.3 MPa (approx. 43 psi)																														
Brush or Roller	Only for touch up																														
Mixing Ratio	One component																														
Thinner	FOXANER 004																														
Surface Temperature	Should be 10 ^o C – 49 ^o C, at least 3 ^o C above the dew point to prevent condensation																														
Drying Time																															
Touch Dry	30 minutes at 25 ^o C, 20 minutes at 32 ^o C																														
Over Coating	16 hours at 25 ^o C, 12 hours at 32 ^o C																														
For Service	1 hour at 32 ^o C, followed by minimum 2 hours at 150 ^o C																														
SAFETY PRECAUTION	<p><i>Keep away from heat, spark and open flames. Avoid breathing of vapour on skin and eye contact. Keep container closed and store in cool, ventilated area when not in use. Proper ventilation and protective measures must be provided during mixing, application and drying, to keep vapour concentration within safe limits and to protect against toxic hazard. Necessary safety equipment must be used and ventilation requirements carefully observed, especially in confined or enclosed spaces, such as tank interior and building.</i></p>																														
DISCLAIMER	<p><i>The information in this product data sheet is given to the best of our knowledge based on laboratory testing and practical experience. If the product is used under condition beyond our control, we cannot guarantee anything but the quality of the products it self. The information in this product data sheet is liable for modification from time to time in the light of experience and our policy of continuous product development, and without further notice</i> .ISSUED: January 2009</p>																														