

FOXASHIELD (FO-302)

Acrylic Emulsion - Exterior

DESCRIPTION FOXASHIELD is high quality, 100% acrylic based emulsion paint that contains no lead and mercury.

PRINCIPLE CHARACTERISTIC

- Designed with special formulation of anti fungus and weather resistance.
- Excellent adhesion.
- High durability.
- High coverage and spreading rate properties.
- Could be wash / wipe, not fading and smelly.

RECOMMENDED USE

Suitable for new / previously painted surfaces such as bricks, asbestos, cement plaster, hardboard, plywood, concrete block, etc.

SYSTEM SPECIFICATION

Alkaline and new surface :

Primer (1 coat) : FOXASEALER WB : FO-101

Finish (2-3 coat) : FOXASHIELD : FO-302

Normal maintenance :

Finish (2-3 coat) : FOXASHIELD : FO-302

SPECIFICATION DATA AT 20°C

Gloss	Eggshell
Colours	See colour card
Specific gravity	1.40 ± 0.2 kg/litre
Solids by volume	45 ± 2%
Coverage theoretical	Varies considerably according to the roughness And porosity of the surface 10 – 12 m ² / litre (on Smooth surfaces of average porosity)
Drying time	Touch dry : 30 minutes (depend on temperature and humidity) Hard dry : 2 hours
Painting interval	Min. 1 hours
Shelf life	12 month (cool and dry place)

SURFACE PREPARATION

- Allow the new surfaces to dry out completely. Remove all loose or defective paint by thorough brushing and scrapping, using a stiff fibre brush or high pressure water jet.
- A good surface preparation is improve performance / life service.
- Make a good minor defect with a suitable grade filler (FOXAFILLER) for holes or cracks (for interior painting only).
- Surface after thorough preparation should be sealed with FOXASEALER.
- NOTE : Do not apply during wet weather.

INSTRUCTION FOR USE

- Stir well before use, to achieve uniformity of colour and good homogeneity.
- It is recommended to apply two (2) layers, in order to get better result.
- Clean all equipment with clean water immediately after use.